

Stackable High Voltage Lithium Battery

SAS51200-HV

51.2V 200Ah

LFP Battery



PRODUCT FEATURE



HIGH CYCLE LIFE

Can achieve 6000 cycles at 90% state of charge, effectively reducing total cost of ownership.



FAST CHARGING SPEED

High charge and discharge efficiency, reducing equipment downtime and saving more time.



HIGHLY ADAPTABLE

Strong environmental adaptability, can withstand up to 60°C.



SAFER

Real-time monitoring of PDU for better system protection.



EASY TO STORE

Due to its extremely low self-discharge rate (LSD) and no risk of sulfation, it can last up to 6 months.



EASY TO STORE

Lithium batteries provide more watt-hours per kilogram while weighing only one-third of their SLA equivalents.



Email: info@sailsolarpv.com Web: www.sailsolarpv.com www.sailsolares.com
Add: Cross Border E-Commerce Supervision Zone, Yulei Road, Hefei, Anhui, China

HIGH VOLTAGE LITHIUM BATTERY

DATASHEET

MODEL

Battery Type	LiFePO4			
Nominal Battery Energy	10.24kWh			
Nominal Capacity	200Ah			
Nominal Voltage	51.2V			
Net Weight	91.2kg			
Dimension(W/D/H)	685*478*278mm			
Communication	RS232/RS485/CAN/BLUETOOTH/WIFI			
Cycle Life*	6000 cycles 80% DOD,0.5C			
Protection Level	IP20			
Expansion	Up to 15 units in series			
Compatible Inverters	Deye/GoodWe/Solis/SAJ/Sinexcel/Hoymiles/Growatt/Ecatus/Sermatec/ATESS/Sunways etc.			
Certification & Safety Standard	UN38.3, MSDS, IEC62619, CE, UL1973, UL2054			
Stackable Type	SAS-71.68kWh-Z	SAS-81.92kWh-Z	SAS-92.16kWh-Z	SAS-102.4kWh-Z
Battery Module Quantity	7units	8units	9units	10units
Nominal Battery Energy	71.68kWh	81.92kWh	92.16kWh	102.4kWh
Nominal Capacity	200Ah	200Ah	200Ah	200Ah
Nominal Voltage	358.4V	409.6V	460.8V	512V
Max.Power Output	71.68kW	81.92kW	92.16kW	102.4kW
Discharge Cut-off Voltage	308V	352V	396V	440V
Charge Cut-off Voltage	397.6V	454.4V	511.2V	568V
Recommend Charging Current	100A	100A	100A	100A
Recommend Discharging Current	100A	100A	100A	100A
Max Charge/Disharge Working Current (A)	200A	200A	200A	200A
Net Weight	638.4KG	729.6KG	820.8KG	912KG
Working temperature	Charge : 0 ~ 55 C / Discharge : -20 C ~ 55 C			
Design Life	10 years+			

*File version: 2026V1-EN

*Weight and Size of the battery module is based on the actual product,

*Specifications may vary during continuous improvements, pls contact us for latest details.

*The installation of battery packs is related to product quality assurance, safe and stable operation. Please follow the requirements of the user manual for standardized installation, use, and routine maintenance

*Each column can hold a maximum of 5 batteries plus one high-voltage box, please confirm the number of batteries per column with the sales team

